



## Blockout Banner 440gsm

This material is 440 g/m<sup>2</sup> super smooth, low curl and prints beautifully! The recommended choice for long lasting, beautiful eye catching graphics. Blockout Banner is a high quality coated PVC Banner for indoor and outdoor advertisements. The light blocking layer in between and unique surface treatment provides 100% opacity with no show through of pictures. The product has a smooth matt surface that delivers superior ink adhesion.

<b>Trägergewebe</b> Base fabric Tissu	(DIN ISO 2076)	<b>Markenpolyester</b> Trade mark polyester Polyester de marque
<b>Garnfeinheit (K/S)</b> Yarn (W/F) Titre (ch/tr)	(DIN EN ISO 2060)	<b>275/275 dtex</b>
<b>Fadendichte</b> Threads Nombre de fils	(DIN EN 1049-2)	<b>15/14 (K/S pro cm)</b> 38/36 (W/F per inch) 15/14 (ch/tr par cm)
<b>Gewebegewicht</b> Basecloth weight Poids du tissu	(DIN EN 12127)	<b>ca. 83 g/m<sup>2</sup></b> approx. 2,5 oz/yd <sup>2</sup>
<b>Beschichtungsmaterial</b> Coating material Matériel pour l'enduction		<b>PVC</b>
<b>Flächengewicht</b> Total weight Poids total du tissu enduit	(DIN EN ISO 2286-2)	<b>ca. 440 g/m<sup>2</sup></b> approx. 13 oz/yd <sup>2</sup>
<b>Reißfestigkeit</b> Tensile strength Résistance à la déchirure	(DIN EN ISO 1421)	<b>1244/1135 N/5 cm</b> 280/255 lbs/2 inch
<b>Weiterreißfestigkeit (K/S)</b> Tear restistance (K/S) Résistance à la déchirure amorcée (ch/tr)	(DIN 53363)	<b>125/114 N</b> 28/26 lbs
<b>Schweißnahthaftung</b> Welding adhesion Adhérence de la soudure	(IVK 3.13)	<b>48 N/5cm</b> 11 lbs/2 inch
<b>Dicke</b> Thickness Épaisseur	(DIN EN ISO 2286-2)	<b>ca. 0,310 mm</b>
<b>Breite</b> Width Largeur		<b>Bis zu 3,2 m</b> Up to 3,2 m Jusqu'à 3,2 m